



HP Designjet T1300 PostScript® ePrinter

Reliable, web-connected, 44-inch PostScript ePrinter for GIS



Do more in less time

- Print on different paper types and sizes seamlessly—and save time—using two rolls with smart switching.
- Print quickly without sacrificing quality. Create an A1/D-size print in 28 seconds with Economode.
- Expect great results with six Original HP inks that deliver dark blacks, true neutral grays, and vivid colors.
- Print confidently with remote job queue, job submittal, and accounting features from the Embedded Web Server.

Easy, powerful printing

- Get trusted, secure connectivity with built-in Gigabit Ethernet, advanced access control, and IPv6 and IPsec.
- Process files in parallel for efficient printing with a 160 GB hard disk.
- Print TIFF, JPEG, and PDF files from your printer's touchscreen or a USB thumb drive—no computer required.
- Rely on true print previews from the driver to quickly and accurately complete your work.

Print from virtually anywhere¹

- Use your Apple® or Android™ smartphone or tablet to print from virtually anywhere¹.
- Access and print projects when you're away from your studio, using HP Designjet ePrint & Share¹.
- Automatically save copies of your work to the cloud when you print using HP Designjet ePrint & Share¹.
- Email projects to your HP Designjet T1300 ePrinter and print, thanks to its web-connectivity features¹.

¹ Requires an HP Designjet ePrint & Share account, Internet connection to the printer, and connected Internet-capable device. When using the HP Designjet ePrint & Share mobile app, a compatible Apple® iOS or Android™ device and Internet connection are required. Data or connection charges may apply. Print times may vary. 2 GB of temporary storage per account. For more information, visit hp.com/go/eprintandshare.

Eco Highlights

- Save paper with automatic print settings and two-roll configuration
- Less ink wasted due to efficient installation and maintenance routines
- Free, convenient HP ink cartridge and printhead recycling¹
- FSC®- and PEFC™-certified HP papers

¹ Program availability varies. Please check hp.com/recycle for details.

Please recycle large-format printing hardware and printing supplies.
Find out how at our website: hp.com/ecosolutions



Technical specifications

Print	Line drawings ²	28 sec/page on A1/D, 103 A1/D prints per hour	
	Color images ³	Fast: 41 m ² /hr (445 ft ² /hr) on coated media Best: 3.1 m ² /hr (33.3 ft ² /hr) on glossy media	
	Print resolution	Up to 2400 x 1200 optimized dpi from 1200 x 1200 input dpi and Optimization For Photo Paper selected	
	Margins (top x bottom x left x right)	Roll: 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) (borderless on photo papers) Sheet: 5 x 17 x 5 x 5 mm (0.2 x 0.67 x 0.2 x 0.2 in)	
	Technology	HP Thermal Inkjet	
	Ink types	Dye-based (C, G, M, pK, Y); pigment-based (mK)	
	Ink drop	6 pL (C, G, M, pK); 9 pL (mK, Y)	
	Printheads	3 (G & pK, mK & Y, M & C)	
	Line accuracy	+/- 0.1% ⁴	
	Minimum line width	0.02 mm (0.0008 in) (HP-GL/2 addressable)	
	Guaranteed minimum line width	0.06 mm (0.0024 in) (ISO/IEC 13660:2001(E)) ⁵	
	Media	Handling	Sheet feed, two automatic roll feeds, automatic roll-switching, automatic cutter
		Weight	60 to 328 g/m ²
Size		210 to 1118-mm (8.3 to 44-in) wide sheets; 279 to 1118-mm (11 to 44-in) rolls	
Thickness		Up to 0.8 mm (31.5 mil)	
Memory	32 GB (virtual) ⁶ , 160 GB hard disk		
Connectivity	Interfaces (standard)	Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified, EIO Jetdirect accessory slot	
	Print languages (standard)	Adobe® PostScript® 3™, Adobe PDF 1.7, HP-GL/2, TIFF, JPEG, CALS G4, HP PCL 3 GUI	
	Drivers (included)	HP-GL/2, HP-RTL drivers for Windows® (optimized for AutoCAD 2000 and higher); HP PCL 3 GUI driver for Mac OS X; PostScript Windows, Linux, and Mac drivers	
Dimensions (w x d x h)	Printer	1770 x 721 x 1050 mm (69.7 x 28.4 x 41.3 in)	
	Shipping	1930 x 766 x 770 mm (76 x 30.2 x 30.3 in)	
Weight	Printer	86 kg (189 lb)	
	Shipping	109 kg (240 lb)	
What's in the box	HP Designjet T1300 Printer, printheads, introductory ink cartridges, printer stand, spindle, quick reference guide, setup poster, startup software, power cord		
Environmental ranges	Operating temperature:	5 to 40°C (41 to 104°F)	
	Storage temperature:	-25 to 55°C (-13 to 131°F)	
	Operating humidity:	20 to 80% RH	
Acoustic	Sound pressure:	43 dB(A) (active); 29 dB(A) (standby)	
	Sound power:	6.1 B(A) (active); 4.7 B(A) (standby)	
Power consumption	< 120 watts (printing); < 27 watts (ready); < 7 watts (< 25 watts with embedded Digital Front End) (sleep); 0.1 watts (off)		
	Input voltage (auto ranging)	100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max	
Certification	Safety	USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS)	
	Electromagnetic	Compliant with Class A requirements, including USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC)	
	Environmental	ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, FEMP	
Warranty	One-year limited hardware warranty		

² Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (Bond) and Original HP inks.

³ Mechanical printing time with Original HP inks.

⁴ +/-0.1% of the specified vector length or +/-0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Matte Film and HP Original HP inks.

⁵ Measured on HP Matte Film.

⁶ Based on 640 MB RAM.



For more information, please visit
hp.com/go/DesignjetT1300

© Copyright 2012-2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Adobe PostScript 3 and PostScript are trademarks of Adobe Systems Incorporated. Windows is a U.S. registered trademark of Microsoft Corporation. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. PANTONE is the property of Pantone, Inc. Apple is a trademark of Apple Computer, Inc., registered in the U.S. and other countries.

4AAA-1671ENW, February 2014

Ordering information

Product	CR652A	HP Designjet T1300 44-in PostScript ePrinter	
Accessories	CN538A	HP Designjet 3-in Core Adapter	
	Q6709A	HP Designjet 44-in Roll Feed Spindle	
	CQ654B/ CQ654C	HP Designjet HD Scanner	
	J8025A	HP Jetdirect 640n Print Server	
	A9D02A	SCP reprocontrol with Folder Driver for HP	
Original HP printheads	C9380A	HP 72 Gray and Photo Black Printhead	
	C9383A	HP 72 Magenta and Cyan Printhead	
	C9384A	HP 72 Matte Black and Yellow Printhead	
Original HP ink cartridges	C9397A	HP 72 69-ml Photo Black Ink Cartridge	
	C9398A	HP 72 69-ml Cyan Ink Cartridge	
	C9399A	HP 72 69-ml Magenta Ink Cartridge	
	C9400A	HP 72 69-ml Yellow Ink Cartridge	
	C9401A	HP 72 69-ml Gray Ink Cartridge	
	C9403A	HP 72 130-ml Matte Black Ink Cartridge	
	C9370A	HP 72 130-ml Photo Black Ink Cartridge	
	C9371A	HP 72 130-ml Cyan Ink Cartridge	
	C9372A	HP 72 130-ml Magenta Ink Cartridge	
	C9373A	HP 72 130-ml Yellow Ink Cartridge	
	C9374A	HP 72 130-ml Gray Ink Cartridge	
	CH575A	HP 726 300-ml Matte Black Designjet Ink Cartridge	
	Original HP large format printing materials	C1861A	HP Bright White Inkjet Paper (FSC® certified) ♻️ 914 mm x 45.7 m (36 in x 150 ft)
		C6020B	HP Coated Paper (PEFCT™ certified) ♻️ 914 mm x 45.7 m (36 in x 150 ft)
		C6030C	HP Heavyweight Coated Paper (PEFCT™ certified) ♻️ 914 mm x 30.5 m (36 in x 100 ft)
Q8808A		HP Premium Satin Photo Paper (FSC® certified) ⁷ 914 mm x 22.9 m (36 in x 75 ft)	
Service and support	HP578E	HP 3 year Next Business Day Onsite Support	
	HP579E	HP 3 year 4-hour response, 13x5 Onsite Support ¹⁰	
	HP580E	HP 3 year 4-hour response, 9x5 Onsite Support ¹⁰	
	HP587E	HP 3 year Next Business Day Onsite Support with Defective Media Retention ¹¹	
	HP592PE	HP 1 year Post Warranty, Next Business Day Onsite Support	
	HP594PE	HP 1 year Post Warranty, 4-hour response, 13x5 Onsite Support ¹⁰	
	HP595PE	HP 1 year Post Warranty, Next Business Day Onsite Support with Defective Media Retention ¹¹	
	H4518E	HP Network Installation Service	
H7604E	HP Installation and Startup Service		

HP Designjet Support Services offer solutions for business critical environments — installation, extended support and maintenance, as well as variety of value added services.

For more information, please visit hp.com/go/designjet/support.

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks and true neutral grays¹¹. For more information, visit hp.com/go/OriginalHPInks.

For the entire HP Large Format Printing Materials portfolio, please see globalBMG.com/hp.

⁷ FSC® trademark license code FSC®-C017543, see fsc.org. PEFC™ trademark license code PEFC™/29-31-198, see pefc.org. Not all FSC®- or PEFC™-certified products are available in all regions.

⁸ Can be recycled through commonly available recycling programs.

⁹ Not available in North America and Latin America.

¹⁰ Not available in Europe, Middle East and Africa.

¹¹ Applicable to HP Designjet T-series Printers, ePrinters, and eMFPs. True neutral grays produced by printers compatible with the HP Three-black ink set.

